

GOSAFE

# G1C+EASY

## ECONOMICAL TRACKER



### APPLICATIONS



Fleet  
Management



Asset  
Management



Transportation  
& Logistic



Insurance  
Telematics

**Gosafe®**

your trusted partner



# G1C+ EASY INSTALL

## KEY FEATURE

- Wide operating voltage range +9~90VDC
- Water resistant, IP65 compliant
- Assisted GPS
- Easy Install
- Driving Behavior
- Trip detection

## YOUR BENEFIT

- Extend Your Product Portfolio
- Enhance Services Optimizations
- Use State-of-the Art Technology to Increase Efficiency



## Easy Install

G1C+Easy Install is a two-wire tracking device that can connect the battery terminal directly. Built-in accelerometer offers trip detection, driving behavior, and turn by location—an ideal solution for insurance telematics, rental and leasing, and light vehicles.

## Features



4G connectivity with  
fallback 2G



Easy Install



Crash Data



Highly Sensitive GPS



Dedicated Digital Input  
for SOS



Driver behavior  
monitoring

# SPECIFICATIONS

## GENERAL

Communication modes	LTE-CAT1/GPRS
Location Technology	50 channels GPS
Operation Voltage	DC9~ 90V

## CELLULAR

Data Support	SMS, TCP, UDP
Operating Bands	2G 900/1800 MHz 4G FDD-LTEB1/B3/B5/B8 EMEA Version B1/B3/B5/B8 South America Version B2/B4/B8/B28
Transmitting power	GSM900:Class 4 (33dBm±2dB) DCS:1800(30dBm±2dB) CAT-1FDD:(23dBm±2dB)

## INTERFACE

Power supply	(Red) +9~32 VDC
Gnd	(Black) Ground
SIM Access	Internal SIM Card 3FF
Switch	Battery ON and OFF Switch
Cellular Antenna	Internal only
LED Indicator	Cellular/GPS Indicator

## PHYSICAL


Dimensions	73x33x13mm
Weight	1.06oz(30g)

## GPS

Tracking Sensitivity	-162 dBm
Acquisition Sensitivity	-147 dBm
Location Accuracy	<10m
TTFF (Open sky)	Cold start 29s average
Hot Start	1 Sec
GPS Antenna	Internal Patch Antenna

## ELECTRICAL

Voltage Range	DC9~ 90V
Backup Battery	Lasting 0.5 hours (3.7V /50mAh Li-battery)
Power Consumption	25mA @12V (working) 10mA @12V (Static)
Backup Battery	LI-PO 50mAh (Optional) Battery Recharging Range is 0 to +45°C




## ENVIRONMENTAL

Temperature	-25 to + 75 °C (working) -40 to + 85 °C (storage)
Humidity	95% R.H. @ 50C non-condensing
IP Rating	IPX5



# Applications



## Ordering Models

Model	Connectivity	Region
G1C+easy-LTA	LTE CAT-1	LATAM Version
G1C+easy-LT	LTE CAT-1	EMEA-ANZ Version
G1C+easy	2G	World wide

### Gosafe Company Limited

+86 (20) 8200-6896

info@gosafesystem.com

www.gosafesystem.com

RM C1-1103-1104, Innovation Building, No.182 Kexue Ave.,

Science & Tech City, Guangzhou-510663, China